

Claims:

1. A method of determining a stereo disparity between a reference image and a search image for a reference pixel in the reference image, said method comprising the steps of:

(a) calculating a similarity measure between a reference window including a set of pixels centering on the reference pixel and each of a group of search windows in the search image which is of a same shape with the reference window and displaced from the reference window within a predetermined search range, wherein a matching pixel count, which is the number of pixels in the reference window which are similar in intensity to corresponding pixels in a search window, is used as the similarity measure between the reference window and said search window; and

(b) determining a displacement between the reference window and a search window which yields a largest similarity measure as the stereo disparity for the reference pixel.

2. A method of determining a stereo disparity as defined in Claim 1, wherein $R(x,y)$ represents the reference pixel, the reference window includes $W_x \times W_y$ pixels centering on $R(x,y)$, W_x and W_y being predetermined numbers, each of the search windows includes $W_x \times W_y$ pixels centering on $L(x+d, y)$ which is a pixel in the search image, d ranging from 0 to a predetermined number S_r , and

said step (a) includes:

(a1) calculating $P(x,y,d)$ values as follows:

$$P(x,y,d) = 1, \text{ if } \text{abs}(B_R(x,y) - B_L(x+d,y)) \leq Th \\ = 0, \text{ otherwise,}$$

where $B_R(x,y)$ and $B_L(x+d,y)$ represent intensity values of $R(x,y)$ and $L(x+d, y)$ and Th is a predetermined threshold; and

(a2) determining $MPC(x,y,d)$ values for $d=0$ to S_r as follows:

$$MPC(x, y, d) = \sum_w P(x, y, d)$$

wherein w represents the reference window and the search window centering on $L(x+d, y)$; and

said step (b) includes selecting a d value which yields a largest $MPC(x, y, d)$ value as the stereo disparity for $R(x, y)$.

3. An apparatus for determining a stereo disparity between a reference image and a search image for a reference pixel in the reference image, said apparatus comprising:

(a) first means for calculating a similarity measure between a reference window including a set of pixels centering on the reference pixel and each of a group of search windows in the search image which is of a same shape with the reference window and displaced from the reference window within a predetermined search range, wherein a matching pixel count, which is the number of pixels in the reference window which are similar in intensity to corresponding pixels in a search window, is used as the similarity measure between the reference window and said search window; and

(b) second means for determining a displacement between the reference window and a search window which yields a largest similarity measure as the stereo disparity for the reference pixel,

wherein $R(x, y)$ represents the reference pixel, the reference window includes $W_x * W_y$ pixels centering on $R(x, y)$, W_x and W_y being predetermined numbers, each of the search windows includes $W_x * W_y$ pixels centering on $L(x+d, y)$ which is a pixel in the search image, d ranging from 0 to a predetermined number S_r , and

said first means includes:

(a1) a P-unit for calculating $P(x, y, d)$ values as follows:

$$P(x, y, d) = 1, \text{ if } \text{abs}(B_R(x, y) - B_L(x+d, y)) \leq Th$$

= 0, otherwise,

where $B_R(x,y)$ and $B_L(x+d,y)$ represent intensity values of $R(x,y)$, and $L(x+d,y)$ and Th is a predetermined threshold value;

(a2) a P-buffer for storing $P(x,y,d)$ values from said P-unit;

(a3) third means for determining $MPC(x,y,d)$ values for $d=0$ to Sr as follows:

$$MPC(x,y,d) = \sum_w P(x,y,d)$$

where w represents the reference window and the search window centering on $L(x+d,y)$; and

said second means includes means for selecting a d value which yields a largest $MPC(x,y,d)$ value as the stereo disparity for $R(x,y)$.

4. An apparatus as defined in Claim 3, wherein said third means includes $(Sr+1)$ MPC-units, each of which determines $MPC(x,y,d)$ for each d value.

5. An apparatus as defined in Claim 4, wherein each of said MPC-units includes:

means for determining $V(x,y,d)$ values which is represented as follows:

$$V(x,y,d) = \sum_{i=-wy}^{wy} P(x,y+i,d)$$

where wy is $(Wy-1)/2$;

means for generating a $MPC(x,y,d)$ value by using $V(x,y,d)$ values as follows:

$$MPC(x, y, d) = \sum_{i=-wx}^{wx} V(x+i, y, d), \text{ if } x=wx \text{ and}$$

$MPC(x, y, d) = MPC(x-1, y, d) + V(x+wx, y, d) - V(x-1-wx, y, d),$ if $x > wx,$
where wx is $(Wx-1)/2$.

6. An apparatus as defined in Claim 5, further comprising a V-buffer for storing the $V(x, y, d)$ values from said V determining means and providing the stored $V(x, y, d)$ values to said MPC generating means.

7. An apparatus as defined in Claim 6,
wherein said V determining means includes:
a V_MP counter for determining $V(x, y, d)$ values for
by summing P values as follows:

$$V(x, y, d) = \sum_{i=-wy}^{wy} P(x, y+i, d)$$

a V_MP update unit for determining $V(x, y, d)$ values
by using $V(x, y-1, d)$ and P values as follows:

$$V(x, y, d) = V(x, y-1, d) + P(x, y+wy, d) - P(x, y-1-wy, d); \text{ and}$$

a multiplexor for selectively providing the $V(x, y, d)$
value from the V_MP counter if $y=wy$ and the $V(x, y, d)$ value from
the V_MP update unit if $y \geq wy$; and

said MPC generating means includes:

a W_MP count and update unit for generating a
 $MPC(x, y, d)$ value by using $V(x, y, d)$ values; and

a multiplexor for selectively providing $V(x, y, d)$
values from the V-buffer or 0 to the W_MP count and update unit
as the $V(x-1-wx, y, d)$ value.

8. An apparatus as defined in Claim 7, wherein

said V_MP counter includes a plurality of full adders;

said V_MP update unit includes:

logic gates for providing $P(x, y+wy, d) - P(x, y-1-wy, d)$;

and

5 full adders for adding the output from the logic gates to $V(x, y-1, d)$, thereby providing $V(x, y, d)$; and

said W_MP count and update unit includes:

means for deciding $V(x+wx, y, d) - V(x-1-wx, y, d)$; and

10 means for adding the output from said deciding means to $MPC(x-1, y, d)$.

9. An apparatus as defined in Claim 3, wherein said P-unit includes:

15 (Sr+1) D_R units each of which stores $L(x+d, y)$ values for each d; and

(Sr+1) D_P units which provides (Sr+1) $P(x, y, d)$ values for $d=0$ to Sr simultaneously in response to $R(x, y)$ and (Sr+1) $L(x+d, y)$ values from the D_R units.

20 10. An apparatus as defined in Claim 9, wherein the D_P unit includes:

means for calculating $(B_L(x+d, y) - B_R(x, y))$ which includes a plurality of full adders;

25 means for calculating an absolute value of $(B_L(x+d, y) - B_R(x, y))$ which includes a plurality of exclusive OR gates; and

means for subtracting the absolute value from Th and providing 0 or 1 depending on the result of the subtraction, which includes a plurality of carry generators.

30 11. An apparatus as defined in Claim 3, further comprising means for selecting a largest one among the $MPC(x, y, d)$ values for $R(x, y)$ and providing a d value yielding the largest MPC value as the disparity for $R(x, y)$.

35 12. An apparatus as defined in Claim 3, where said P-buffer includes means for storing $I_x * W_y * (Sr+1)$ P values, wherein I_x is the number of pixels in a row in the reference and the

search image.

- 5 13. An apparatus as defined in Claim 6, where said V-buffer includes means for storing $I_x \cdot (S_r + 1)$ V values, wherein I_x is the number of pixels in a row in the reference and the search image.